



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>4</sup> :</b> <b>C03C 13/00, 13/02, 25/06</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 89/12032</b> <b>(43) International Publication Date:</b> 14 December 1989 (14.12.89)
<b>(21) International Application Number:</b> PCT/US89/02288 <b>(22) International Filing Date:</b> 25 May 1989 (25.05.89) <b>(30) Priority data:</b> 201,513 1 June 1988 (01.06.88) US <b>(71) Applicant:</b> MANVILLE SALES CORPORATION [US/ US]; Manville Plaza, 5th Floor, P.O. Box 5108, Denver, CO 80217 (US). <b>(72) Inventors:</b> OLDS, Leonard, Elmo ; 977 South Lake Gulch Road, Castle Rock, CO 80104 (US). KIELMEYER, Wil- liam, Henry ; 3374 West Chenango Avenue, Englewood, CO 80110 (US). <b>(74) Agent:</b> SCHRAMM, William, J.; Brooks & Kushman, 2000 Town Center, Suite 2000, Southfield, MI 48075 (US).		<b>(81) Designated States:</b> AT (European patent), AU, BE (Euro- pean patent), BR, CH (European patent), DE (European patent), DK, FI, FR (European patent), GB (European patent), IT (European patent), JP, KP, KR, LU (Euro- pean patent), NL (European patent), NO, SE (European patent).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>
<b>(54) Title:</b> PROCESS FOR DECOMPOSING AN INORGANIC FIBER  <b>(57) Abstract</b>  Inorganic fibers which have a silicon extraction of greater than 0.02 wt% Si/day in physiological saline solutions. The fiber contains SiO <sub>2</sub> , MgO, CaO, and at least one of Al <sub>2</sub> O <sub>3</sub> , ZrO <sub>2</sub> , TiO <sub>2</sub> , B <sub>2</sub> O <sub>3</sub> , iron oxides, or mixtures thereof. Also disclosed are inorganic fibers which have diameters of less than 3.5 microns and which pass the ASTM E-119 two hour fire test when processed into a fiber blanket having a bulk density in the range of about 1.5 to 3 pcf.		

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	ML	Mali
AU	Australia	FR	France	MR	Mauritania
BB	Barbados	GA	Gabon	MW	Malawi
BE	Belgium	GB	United Kingdom	NL	Netherlands
BF	Burkina Fasso	HU	Hungary	NO	Norway
BG	Bulgaria	IT	Italy	RO	Romania
BJ	Benin	JP	Japan	SD	Sudan
BR	Brazil	KP	Democratic People's Republic of Korea	SE	Sweden
CF	Central African Republic	KR	Republic of Korea	SN	Senegal
CG	Congo	LI	Liechtenstein	SU	Soviet Union
CH	Switzerland	LK	Sri Lanka	TD	Chad
CM	Cameroon	LJ	Luxembourg	TG	Togo
DE	Germany, Federal Republic of	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

PROCESS FOR DECOMPOSING AN INORGANIC FIBER  
-----

FIELD OF INVENTION

This invention relates to inorganic fiber compositions and more particularly it relates to inorganic fiber compositions which can contain silica, magnesia, calcium oxide, alumina, and other oxides. Some of the inventive fibers have excellent fire ratings, some have especially low durabilities in physiological saline solutions, and some have combinations of these foregoing properties.

BACKGROUND OF THE INVENTION

For many years, inorganic fibers generically referred to in the industry as "mineral wool fibers", made from slag, rock, fly ash, and other by-product raw materials have been manufactured. These fibers have been typically manufactured by melting the slag, rock, etc., containing such oxides as silica, alumina, iron oxide (ferrous and ferric), calcium oxide, and magnesia; allowing the molten material to be blown by gas or steam or to impinge on rotors at high speeds; and causing the resulting blown or spun fibers to be accumulated on a collecting surface. These fibers are then used in bulk or in the form of mates, blankets, and the like as both low and high temperature insulation. U.S. Patent No. 2,576,312 discloses a conventional mineral wool composition and method for making the same.

In the past, the industry has well recognized the standard drawbacks associated with conventional mineral wool fibers. Conventional mineral wool fibers may have high contents of undesired oxides which often

-2-

detract from their refractory properties. The conventional mineral wools are coarse, i.e. they have average fiber diameters of 4 to 5 microns (measured microscopically) and have high shot contents in the range of 30 to 50 weight percent. The coarseness of the fiber reduces the insulating value of the fiber and makes conventional mineral wool unpleasant to handle and unfriendly to the touch. For example, because of their coarse fiber diameters, conventional mineral wool blankets must have bulk densities of from 4 to 8 pcf and even higher in order to pass the ASTM E-119 two hour fire test. On the other hand, fiber glass blankets are often made with bulk densities of 2 pcf or lower. While the fiber glass blankets are friendly because of their low bulk densities and relatively fine fiber diameter, they do not have sufficient fire resistance so as to pass even the one hour ASTM E-119 fire test.

Recently, another potential problem with traditional mineral wool and other types of fiber has been recognized. It is well known that inhalation of certain types of fiber can lead to elevated incidence of respiratory disease, including cancers of the lung and surrounding body tissue. Several occurrences are well-documented in humans for several types of asbestos fiber. Although for other varieties of natural and manmade mineral fiber direct and unequivocal evidence for respiratory disease is lacking, the potential for such occurrence has been inferred from results of tests on laboratory animals. In the absence or insufficiency of direct human epidemiological data, results from fiber inhalation or implantation studies on animals provides the best "baseline information" from which to extrapolate disease potential.

**SUBSTITUTE SHEET**

-3-

Chronic toxicological studies on animals have, however, been able to statistically demonstrate the importance of three key factors that relate directly to the potential for respiratory disease and especially carcinoma: (a) dose of fiber received (including time of exposure); (b) dimension of the inhaled fiber; and (c) persistence of the fiber within the lung. The effects of dose and dimension have been well-characterized from such studies and as a result are fairly well known in regard to human disease potential. The dose is obviously a product of the environment in which the fiber is used and the manner in which it is used. The dimension and persistence of the fiber within the lung, on the other hand, are functions of the manner in which the fiber is formed and of its chemical composition. In general, the smaller the fiber the more likely that it will become embedded in lung tissue when inhaled, thus increasing the danger of respiratory disease.

Although less is known about the link between persistence of the fiber within the lung and respiratory disease, increasing attention is being focused on this aspect of the health issue. Biological persistence refers to the length of time a fiber endures as an entity within the body. The physiochemical concept that most closely relates to persistence and is perhaps more easily quantified is that of "durability" - specifically, the chemical solubility (or resistance to solubility) of fibers in body fluids and the tendency of such fibers to maintain physical integrity within such an environment. In general, the less durable a fiber is, the less will be the potential health risk associated with the inhalation of that fiber. One method of measuring the chemical durability of a fiber in body fluids is to measure its durability in physiological

**SUBSTITUTE SHEET**

-4-

saline solutions. This can be done by quantifying the rate of extraction of a chemical component of the fiber such as silicon into the physiological saline solution over a certain period of time.

5                   Thus, as can be easily concluded from the foregoing discussion, conventional mineral wool fibers have several serious drawbacks. However, even the alternatives to mineral wools have problems. For example, as mentioned earlier glass fibers have a fire  
10 resistance problem and whereas the refractory ceramic fibers have been gaining increasing use in recent years as an alternative to mineral wool fibers because of their ultra-high temperature resistance and superior ability to pass all fire rating tests, their use is  
15 limited by the fact that they are relatively expensive and have a relatively high chemical durability in physiological saline solutions as well.

                  In conclusion, there is a great need in the industry for low cost, friendly feeling low bulk density  
20 inorganic fibers which have good fire resistance properties as measured by their ability to pass the ASTM E-119 two hour fire test. Additionally, there is a tremendous demand for fibers which have especially low durabilities in physiological saline solutions. What would be  
25 particularly advantageous to the industry would be fibers with combinations of the above mentioned sought after properties. Also, advantageous would be fibers which also have excellent refractory properties as well, e.g. high continuous service temperatures.

**SUBSTITUTE SHEET**

-5-

SUMMARY OF THE INVENTION

In one embodiment of the present invention, there are provided inorganic fibers having a silicon extraction of greater than about 0.02 wt% Si/day in physiological saline solutions and a composition consisting essentially of about 0-10 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 35-70 wt%  $\text{SiO}_2$ ; 0-50 wt%  $\text{MgO}$ ; and  $\text{CaO}$ .

In another embodiment of the present invention, there are provided inorganic fibers which have a 5 hour silicon extraction in physiological saline solutions of at least about 10 ppm. These fibers can broadly have compositions consisting essentially of the following ingredients at the indicated weight percentage levels:

0-1.5 wt% of either  $\text{Al}_3\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 40-70 wt%  $\text{SiO}_2$ ; 0-50 wt%  $\text{MgO}$ ; and  $\text{CaO}$

1.5-3 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 40-66 wt%  $\text{SiO}_2$ ; 0-50 wt%  $\text{MgO}$ ; and  $\text{CaO}$

3-4 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 40-64 wt%  $\text{SiO}_2$ ; 0-50 wt%  $\text{MgO}$ ; and  $\text{CaO}$

4-6 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 40-59 wt%  $\text{SiO}_2$ ; 0-25 wt%  $\text{MgO}$ ; and  $\text{CaO}$

6-8 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 35-54 wt%  $\text{SiO}_2$ ; 0-25 wt%  $\text{MgO}$ ; and  $\text{CaO}$

8-10 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 35-45 wt%  $\text{SiO}_2$ ; 0-20 wt%  $\text{MgO}$ ; and  $\text{CaO}$

**SUBSTITUTE SHEET**

-6-

In a preferred embodiment, inventive fibers with 5 hour silicon extractions of greater than about 20 ppm and most preferably greater than about 50 ppm are provided.

5 In another embodiment of the present invention there are provided inorganic fibers having a diameter of less than 3.5 microns and which pass the ASTM E-119 two hour fire test when processed into a fiber blanket having a bulk density in the range of about 1.5 to 3 pcf and having a composition consisting essentially of  
10 about: 0-10 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 58-70 wt%  $\text{SiO}_2$ ; 0-21 wt%  $\text{MgO}$ ; 0-2 wt% alkali metal oxides; and  $\text{CaO}$  and wherein the amount of alumina + zirconia is less than 6 wt% and  
15 the amount of iron oxides or alumina + iron oxides is less than 2 wt%. Preferably, the inventive fibers in this embodiment may have compositions consisting essentially of about:

0-1.5 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron  
20 oxides, or mixtures thereof; 58.5-70 wt%  $\text{SiO}_2$ ; 0-21 wt%  $\text{MgO}$ ; 0-2 wt% alkali metal oxides; and  $\text{CaO}$

greater than 1.5 wt% up to and including 3 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 58.5-66 wt%  $\text{SiO}_2$ ; 0-21 wt%  $\text{MgO}$ ; 0-2 wt% alkali  
25 metal oxides; and  $\text{CaO}$

greater than 3 wt% up to and including 4 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 58-63 wt%  $\text{SiO}_2$ ; 0-8 wt%  $\text{MgO}$ ; 0-2 wt% alkali  
metal oxides; and  $\text{CaO}$

30 greater than 4 wt% up to and including 6 wt% of either  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides, or mixtures thereof; 58-59 wt%  $\text{SiO}_2$ ; 0-7 wt%  $\text{MgO}$ ; 0-2% alkali metal oxides; and  $\text{CaO}$ .

SUBSTITUTE SHEET



-7-

As discussed herein earlier, there has been a demand in the industry for inorganic fibers with an excellent fire rating at low bulk densities and fibers with especially low chemical durabilities in physiological saline solutions. Therefore, each category of inventive fibers should fulfill a real need in the industry and should be available for applications where heretofore low cost, mineral wool type fibers have not been available. What is particularly advantageous about the present invention is the fact that fibers are provided where a special demand exists, i.e. applications in the industry where fibers with both an excellent fire rating and an especially low durability in physiological saline solutions are in demand.

Other features and aspects, as well as the various benefits and advantages, of the present invention will be made clear in the more detailed description which follows.

#### DETAILED DESCRIPTION OF THE INVENTION

The inventive fiber compositions of the present invention can be made from either pure metal oxides or less pure raw materials which contain the desired metal oxides. Table 1 herein gives an analysis of some of the various raw materials which can be used to make inventive fiber compositions. Physical variables of the raw materials such as particle size may be chosen on the basis of cost, handleability, and similar considerations.

Except for melting, the inventive fibers are formed in conventional inorganic fiber forming equipment

**SUBSTITUTE SHEET**

-8-

and by using standard inorganic fiber forming techniques as known to those skilled in the art. Preferably, production will entail electric furnace melting rather than cupola melting since electric melting keeps molten  
5 oxides of either pure or less pure raw materials more fully oxidized thereby producing longer fibers and stronger products. The various pure oxides or less pure raw materials are granulated to a size commonly used for electric melting or they may be purchased already so  
10 granulated.

The granulated raw materials are then mixed together and fed to an electric furnace where they are melted by electric resistance melting with electrodes preferably positioned according to the teachings of U.S.  
15 Patent No. 4,351,054. Melt formation can be either continuous or batchwise although the former is preferred. The molten mixture of oxides is then fiberized as disclosed in U.S. Patent No. 4,238,213.

While the fiberization techniques taught in  
20 U.S. 4,238,213 are preferred for making the inventive fibers, other conventional methods may be employed such as sol-gel processes and extrusion through holes in precious metal alloy baskets.

The fibers so formed will have lengths in the  
25 range of from about 0.5 to 20 cm and diameters in the range of from about 0.05 to 10 microns with the average fiber diameter being in the range of about 1.5 to 3.5 microns. Table 2 shows the average fiber diameter (measured microscopically) and the unfiberized shot  
30 content of various inventive fibers. As may be seen, the average microscopic fiber diameter was 2.3 microns and the average unfiberized shot content was 27%.

**SUBSTITUTE SHEET**

-9-

For purposes of comparison, conventional mineral wool fibers were also tested with the results being given in Table 2 as numbers 226 and 229. These conventional fibers averaged 4.7 microns (measured microscopically) in diameter and had an average 40 wt% shot content. The continuous service temperature ranged from 1370°F to 1490°F, averaging 1420°F.

Table 3 contains an extensive chemical analysis of a number of inventive fibers. Because of the large number of fiber samples containing alumina additives made to the base calcium oxide/magnesia/silica system, only the average analysis of the minor constituent of these fibers are given in Table 3. The silica, alumina, magnesia, and calcium oxide contents for these fibers are given in Table 4.

As used herein, the "service temperature" of an inorganic fiber is determined by two parameters. The first is the obvious condition that the fiber must not soften or sinter at the temperature specified. It is this criterion which precludes the use of glass fibers at temperatures about 800°F to 1000°F (425° to 540°C). Additionally, a felt or blanket made from the fibers must not have excessive shrinkage when soaking at its service temperature. "Excess shrinkage" is usually defined to be a maximum of 5% linear or bulk shrinkage after prolonged exposure (usually for 24 hours) at the service temperature. Shrinkage of mats or blankets used as furnace liners and the like is of course a critical feature, for when the mats or blankets shrink they open fissures between them through which the heat can flow, thus defeating the purpose of the insulation. Thus, a fiber rated as a "1500°F (815°C) fiber" would be defined

SUBSTITUTE SHEET

-10-

as one which does not soften or sinter and which has acceptable shrinkage at that temperature, but which begins to suffer in one or more of the standard parameters at temperatures above 1500°F (815°C).

5           The service temperatures for a representative number of fibers in the inventive compositional range are listed in Table 2. The continuous service temperature for constant silica/magnesia/calcium oxide ratios are given in Table 6. As may be seen in all cases, the  
10       lower the alumina content of the fiber, the higher the service temperature will be, with the highest service temperature being at zero percent alumina for alumina contents less than 30%. Thus to attain the most desired properties of the inventive fiber it is not possible to  
15       accept any of the alumina contents resulting from melting the traditional mineral wool raw materials. Rather, various amounts of sufficiently pure oxides will be required to dilute the alumina contents to the desired low levels. To attain fibers of the highest  
20       service temperatures, only pure raw materials with essentially no significant amounts of alumina must be used.

          A series of inventive fibers were also tested for their silicon extraction in a saline solution  
25       according to the following procedure:

          A buffered model physiological saline solution was prepared by adding to 6 liters of distilled water the following ingredients at the indicated concentrations:

30	<u>Ingredient</u>	<u>Concentration, g/l</u>
	MgCl <sub>2</sub> ·6H <sub>2</sub> O	0.160
	NaCl	6.171

SUBSTITUTE SHEET

-11-

	KCl	0.311
	Na <sub>2</sub> HPO <sub>4</sub>	0.149
	Na <sub>2</sub> SO <sub>4</sub>	0.079
	CaCl <sub>2</sub> ·2H <sub>2</sub> O	0.060
5	NaHCO <sub>3</sub>	1.942
	NaC <sub>2</sub> H <sub>3</sub> O <sub>2</sub>	1.066

Before testing, this solution was buffered to a pH of 7.6 by bubbling with a gaseous mixture of 5% CO<sub>2</sub>/95%N<sub>2</sub>.

10           One half (1/2) gram of each sample of fiber listed in Table 3 was then placed into separate closed, plastic bottles along with 50 cc of the prepared physiological saline solution and put into an ultrasonic bath for 5 hours. The ultrasonic vibration application was  
15 adjusted to give a temperature of 104°F at the end of the 5 hour period. At the end of the test period, the saline solution was filtered and the solution chemically analyzed for silicon content. The silicon concentration in the saline solution was taken to be a measure of the  
20 amount of fiber which solubilized during the 5 hour test period. The CaO and MgO contents of the fiber were similarly solubilized.

One of the inventive fibers was tested for silicon extraction in a physiological saline solution  
25 for periods of up to 6 months. Results were as follows:

SUBSTITUTE SHEET

-12-

Fiber Number	Steady State		Total Amphoteric Oxides in Fiber	Comments On Fiber Residue After 6 Months
	Silicon Extraction in 6 Months	Silicon Extraction Rate For 0.20 m <sup>2</sup> /g Surface Area, % Si/day		
29 (inventive)	96%	0.16%	1.0%	carbonate hydroxyl apatite fiber, disintegrated into small particles
137 (non- inventive)	3%	0.013%	8.9%	slight fine grained fibers with uniform corrosion
235 (non- inventive)	4%	0.012%	25.6%	no fiber corrosion; some surface deposition

SUBSTITUTE SHEET

-13-

Categorization of oxides melts according to scales of acidity or basicity has been well known for many years. (See "A Scale of Acidity and Basicity in Glass," Glass Industry, February 1948, pp 73-74.) We have now found that by strictly controlling the compositions of the oxide melts according to the acidic or basicity behavior of the respective oxides, fibers can be made which are surprisingly soluble in saline solutions. Increasing the content of silica, alumina, and the amphoteric oxides in the fiber increases the acid ratio of the fiber composition. This tends to stabilize the system against silicon extraction by weak solutions as a result of relative changes in the interatomic bonding forces and extension of the silica network. Other amphoteric oxides besides alumina will have an alumina equivalency with respect to extraction by saline solutions. The amphoteric oxides zirconia and titania appear to have an alumina equivalency of close to 1 to 1. We have found that in general for desired high saline solubility the amount of total amphoteric oxides must be kept below about 10% depending upon the amount of silica present. On the other hand, with the exception of iron and manganese oxides, the basic oxides can vary widely since their alumina equivalency is small. However, while iron and manganese oxides are generally considered to be basic in nature, their behavior with respect to saline solubility more closely relate to the amphoteric oxides, thus the amounts of iron and manganese oxides must be similarly limited.

Many of the fibers were tested for their fire resistance according to the following simulated fire rating test procedure:

**SUBSTITUTE SHEET**

-14-

For screening test purposes, a small furnace was constructed using an electrically heated flat-plate element at the back of the heat source. A 6 inch x 6 inch x 2 inch thick sample of 1 3/4 to 6 1/2 pcf density of each formulated fiber was mounted parallel with the element and 1 inch from it. Thermocouples were then positioned at the center of the fiber sample surfaces. A computer was used to control power via a simple on-off relay system to the heating element. The position of the relay was based on the reading of the thermocouple on the sample surface nearest the element and the programmed fire test heat-up schedule.

The furnace was heated so as to follow a standard ASTM E-119 time/temperature curve for the 2-hour test period. In the test utilized herein, failure of the fiber is considered to occur when the furnace is unable to maintain the standard temperature per ASTM E-119 because the fiber insulation has sintered sufficiently to allow heat to escape through the fiber layer.

The results of the testing of the fibers for saline solubility and the two hour ASTM E-119 fire test are given in Table 4 for the fibers made with alumina addition and in Table 5 for the remaining fibers to which other oxidic constituents were added. These additions included:  $B_2O_3$ ,  $P_2O_5$ ,  $TiO_2$ ,  $ZrO_2$ ,  $Fe_2O_3$  +  $MnO$ ,  $La_2O_3$ ,  $Cr_2O_3$ , and  $Na_2O$ . For glass fibers within the scope of the invention to function in an ASTM E-119 fire test, i.e. to withstand the rising temperatures of a simulated fire which can reach 1850°F in two hours, it is necessary that they convert from an amorphous condition to a beneficial pseudo crystalline state during heat-up. The inventive fibers do this but can be assisted in this function by the inclusion of suitable crystal nucleating

**SUBSTITUTE SHEET**



-15-

agents. Such agents may include  $\text{TiO}_2$ ,  $\text{ZrO}_2$ , platinum,  $\text{Cr}_2\text{O}_3$ ,  $\text{P}_2\text{O}_5$ , and others. Such additions are within the scope of this invention.

SUBSTITUTE SHEET

TABLE 1  
RAW MATERIALS USED

Pure Raw Materials					
	<u>Silica Sand</u>	<u>Quick Lime</u>	<u>Calced Dolomite</u>	<u>Aluminum Oxide</u>	<u>Magnesium Oxide</u>
<u>ACIDIC OXIDES</u>					
SiO <sub>2</sub>	99.0	0.34	0.50	0.02	0.4
<u>AMPHOTERIC OXIDES</u>					
TiO <sub>2</sub>	nil	nil	nil	0.002	nil
Al <sub>2</sub> O <sub>3</sub>	0.30	0.26	0.50	98.8	0.1
<u>BASIC OXIDES</u>					
Fe <sub>2</sub> O <sub>3</sub>	0.30	0.05	0.15	0.02	0.7
MnO	--	--	--	--	--
MgO	0.02	0.14	40.0	nil	96.3
CaO	0.03	97.75	57.0	0.01	2.0
Na <sub>2</sub> O	0.04	0.02	0.01	0.30	0.02
K <sub>2</sub> O	0.01	0.01	nil	0.01	0.01
<u>MISCELLANEOUS</u>					
SO <sub>3</sub>	--	--	0.4	--	--
S <sup>=</sup>	--	--	--	--	--
C	--	--	--	--	--
<u>LOI</u>	<u>0.2</u>	<u>0.7</u>	<u>3.0</u>	<u>0.20</u>	<u>1.8</u>
TOTAL	99.90	99.27	101.56	99.36	101.33

SUBSTITUTE SHEET

TABLE 1  
RAW MATERIALS USED (continued)

Less Pure Raw Materials				
	<u>Kaolin</u>	<u>Blast Furnace Slag</u>	<u>Nepheline Syenite</u>	<u>Talc</u>
<u>ACIDIC OXIDES</u>				
SiO <sub>2</sub>	50.5	35.16	61.3	61.2
<u>AMPHOTERIC OXIDES</u>				
TiO <sub>2</sub>	1.61	0.62	0.003	nil
Al <sub>2</sub> O <sub>3</sub>	43.6	12.88	23.4	0.7
<u>BASIC OXIDES</u>				
Fe <sub>2</sub> O <sub>3</sub>	0.80	0.20	0.07	0.85
MnO	--	0.62	--	--
MgO	0.01	16.06	0.05	31.7
CaO	0.04	32.94	0.58	0.19
Na <sub>2</sub> O	0.06	0.45	9.60	--
K <sub>2</sub> O	0.02	0.25	4.50	--
<u>MISCELLANEOUS</u>				
SO <sub>3</sub>	--	0.28	--	--
S=	--	1.03	--	--
C	--	0.30	--	--
<u>LOI</u>	<u>2.90</u>	<u>--</u>	<u>0.62</u>	<u>5.0</u>
<u>TOTAL</u>	<u>99.54</u>	<u>100.79</u>	<u>100.12</u>	<u>99.0</u>

-17-

SUBSTITUTE SHEET

-18-

Silica Sand: Ottawa Silica - Sil-co-Sil Grade 295  
Quick Lime: Mississippi Lime - Pulverized Quick Lime  
Calcined Dolomite: Ohio Lime NO. 16 Burnt Dolomitic Lime  
Aluminum Oxide: Reynolds Calcined Alumina, RC-23  
Magnesium Oxide: Baymag 56 Feed Grade  
Kaolin: American Cyanamide Andersonville Kaolin  
Blast Furnace Slag: Calumite Morrisville Slag  
Nepheline Syenite: Indusmin Grad A400  
Talc: Pfizer Grade MP4426

Additives:

Soda Ash: 58.3%  $\text{Na}_2\text{O}$   
Boric Acid: 55.5%  $\text{B}_2\text{O}_3$   
Magnetite Iron Concentrates: 98.5% Iron Oxides  
Zircon: 66.2%  $\text{ZrO}_2$   
Manganese Oxide: 99%  $\text{MnO}_2$   
Titanium Dioxide: 99%  $\text{TiO}_2$   
Chromium Oxide: 99.5%  $\text{Cr}_2\text{O}_3$   
Lanthanum Carbonate: Moly Corp.

SUBSTITUTE SHEET

-19-

TABLE 3  
COMPOSITION OF FIBERS

TEST NO.	ACIDIC OXIDES			SUB TOTAL	AMPHOTERIC OXIDES				SUB TOTAL
	B <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	P <sub>2</sub> O <sub>5</sub>		TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	ZrO <sub>2</sub>		
Composition of Fibers with Al <sub>2</sub> O <sub>3</sub> additions (minor constituents only)									
1 to	0.00	--	0.00	--	--	0.01	0.01	0.02	
	--	--	--	--	--	--	--	--	
Composition of Fibers with B <sub>2</sub> O <sub>3</sub> additions									
164	0.32	64.8	--	65.12	--	--	--	0.06	
165	0.52	63.9	--	64.42	--	--	--	1.20	
166	0.64	64.6	--	65.24	--	--	--	0.06	
167	0.82	64.5	--	65.32	--	--	--	0.06	
168	1.33	64.1	--	65.43	--	--	--	0.06	
169	1.37	64.1	--	65.47	--	--	--	0.06	
170	2.22	63.6	--	65.82	--	--	--	0.06	
171	8.41	59.6	--	68.01	--	--	--	0.06	
Composition of Fibers with P <sub>2</sub> O <sub>5</sub> additions									
2	--	49.6	6.05	55.65	0.06	0.38	0.04	0.48	
Composition of Fibers with TiO <sub>2</sub> additions									
173	--	48.6	--	48.6	10.0	41.4	--	51.4	
Composition of Fibers with ZrO <sub>2</sub> additions									
174	--	63.5	--	63.5	.01	0.88	0.21	1.10	
175	--	59.2	--	59.2	--	0.33	0.40	0.73	
176	--	59.5	--	59.5	--	0.31	0.42	0.73	

SUBSTITUTE SHEET

-20-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	BASIC OXIDES										SUB TOTAL
	FeO <sub>3</sub>	MnO	La <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	MgO	Li <sub>2</sub> O	CaO	BaO	Na <sub>2</sub> O	K <sub>2</sub> O	
<u>Composition of Fibers with Al<sub>2</sub>O<sub>3</sub> additions (minor constituents only)</u>											
1 to	0.06	0.02	0.00	0.02	--	0.00	--	0.04	0.04	0.01	.19
--	--	--	--	--	--	--	--	--	--	--	--
<u>Composition of Fibers with B<sub>2</sub>O<sub>3</sub> additions</u>											
164	--	--	--	--	8.7	--	26.6	--	--	--	35.3
165	--	--	--	--	8.6	--	26.2	--	--	--	34.8
166	--	--	--	--	8.7	--	26.5	--	--	--	35.2
167	--	--	--	--	8.7	--	26.5	--	--	--	35.2
168	--	--	--	--	8.6	--	26.3	--	--	--	34.9
169	--	--	--	--	8.6	--	26.3	--	--	--	34.9
170	--	--	--	--	8.5	--	26.1	--	--	--	34.6
171	--	--	--	--	8.0	--	24.0	--	--	--	32.0
<u>Composition of Fibers with P<sub>2</sub>O<sub>5</sub> additions</u>											
2	0.21	0.00	--	0.68	11.15	0.00	31.45	0.00	0.05	0.04	43.58
<u>Composition of Fibers with TiO<sub>2</sub> additions</u>											
173	--	--	--	--	--	--	--	--	--	--	--
<u>Composition of Fibers with ZrO<sub>2</sub> additions</u>											
174	--	--	--	--	0.33	--	35.55	--	.03	.01	35.92
175	--	--	--	--	0.41	--	39.1	--	--	--	39.51
176	--	--	--	--	0.42	--	39.1	--	--	--	39.52

SUBSTITUTE SHEET

-21-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	MISCELLANEOUS			TOTAL
	SO <sub>3</sub>	Misc.	SUB TOTAL	
<u>Composition of Fibers with Al<sub>2</sub>O<sub>3</sub> additions (minor constituents only)</u>				
1 to	.05/ .20	.02 --	.07/ .22	.14 .44
<u>Composition of Fibers with B<sub>2</sub>O<sub>3</sub> additions</u>				
164	--	--	--	100.48
165	--	--	--	100.42
166	--	--	--	100.5
167	--	--	--	100.58
168	--	--	--	100.39
169	--	--	--	100.43
170	--	--	--	100.48
171	--	--	--	100.07
<u>Composition of Fibers with P<sub>2</sub>O<sub>5</sub> additions</u>				
2	--	0.02	0.02	99.73
<u>Composition of Fibers with TiO<sub>2</sub> additions</u>				
173	--	--	--	100.0
<u>Composition of Fibers with ZrO<sub>2</sub> additions</u>				
174	--	--	--	100.52
175	--	--	--	99.44
176	--	--	--	99.75

SUBSTITUTE SHEET

-22-

TABLE 3  
COMPOSITION OF FIBERS

TEST NO.	ACIDIC OXIDES				AMPHOTERIC OXIDES			
	B <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	P <sub>2</sub> O <sub>5</sub>	SUB TOTAL	TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	ZrO <sub>2</sub>	SUB TOTAL
Composition of Fibers with ZrO <sub>2</sub> additions (Cont.)								
177	--	59.7	--	59.7	--	0.34	0.50	0.84
8	--	60.0	--	60.0	--	0.36	0.54	0.90
179	--	59.2	--	59.2	--	0.35	0.58	0.93
180	--	54.3	--	54.3	.01	1.29	0.58	1.88
181	--	59.2	--	59.2	--	0.32	0.83	1.15
182	--	46.85	--	46.85	.02	2.03	0.84	2.89
182(a)	--	59.4	--	59.4	--	0.38	2.31	2.69
183	--	59.05	--	59.05	--	0.30	2.65	2.95
184	--	57.96	--	57.96	--	0.42	3.11	3.53
185	--	57.8	--	57.80	--	0.56	3.12	3.68
186	--	59.05	--	59.05	--	0.38	3.27	3.65
187	--	56.88	--	56.88	--	0.32	3.30	3.62
188	--	57.7	--	57.7	--	0.20	3.30	3.50
189	--	58.19	--	58.19	--	0.39	3.36	3.75
190	--	57.86	--	57.86	--	0.36	3.37	3.73
191	--	58.6	--	58.6	--	0.58	3.67	4.25
192	--	58.4	--	58.4	--	0.65	3.69	4.34
193	--	56.65	--	56.65	.02	3.35	4.50	7.87

SUBSTITUTE SHEET



-23-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	BASIC OXIDES										SUB TOTAL
	FeO <sub>3</sub>	MnO	La <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	MgO	Li <sub>2</sub> O	CaO	BaO	Na <sub>2</sub> O	K <sub>2</sub> O	
Composition of Fibers with ZrO <sub>2</sub> additions (Cont.)											
177	--	--	--	--	0.46	--	38.7	--	--	--	39.16
8	--	--	--	--	0.48	--	38.3	--	--	--	38.78
179	--	--	--	--	0.98	--	37.0	--	--	--	37.98
180	.09	.01	--	--	10.20	--	32.75	.01	.04	.02	43.12
181	--	--	--	--	1.13	--	36.6	--	--	--	37.73
182	.08	.01	--	--	20.6	--	29.2	.03	.05	.01	49.98
182(a)	--	--	--	--	2.06	--	34.9	--	--	--	36.96
183	.06	.00	--	.05	3.08	--	34.84	.00	.03	.01	38.07
184	--	--	--	--	3.55	--	35.17	--	--	--	38.72
185	--	--	--	--	3.74	--	34.4	--	--	--	38.14
186	--	--	--	--	2.57	--	36.94	--	--	--	39.51
187	--	--	--	--	4.00	--	36.45	--	--	--	40.45
188	--	--	--	--	3.00	--	36.0	--	--	--	39.0
189	--	--	--	--	3.26	--	35.39	--	--	--	38.65
190	--	--	--	--	3.22	--	35.66	--	--	--	38.88
191	--	--	--	--	2.72	--	33.5	--	--	--	36.22
192	--	--	--	--	2.59	--	33.2	--	--	--	35.79
193	.05	.00	--	.00	3.35	--	31.9	.00	.05	.01	35.36

SUBSTITUTE SHEET

-24-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	MISCELLANEOUS			TOTAL
	SO <sub>3</sub>	Misc.	SUB TOTAL	
<u>Composition of Fibers with ZrO<sub>2</sub> additions (Cont.)</u>				
177	--	--	--	99.70
8	--	--	--	99.68
179	--	--	--	98.11
180	--	.01	.01	99.31
181	--	--	--	98.08
182	--	.02	.02	99.74
182 (a)	--	--	--	99.05
183	--	.02	.02	100.09
184	--	--	--	100.21
185	--	--	--	99.62
186	--	--	--	102.21
187	--	--	--	100.95
188	--	--	--	100.20
189	--	--	--	100.59
190	--	--	--	100.47
191	--	--	--	99.07
192	--	--	--	98.53
193	--	.01	.01	99.89

SUBSTITUTE SHEET

-25-

TABLE 3  
COMPOSITION OF FIBERS

TEST NO.	ACIDIC OXIDES				AMPHOTERIC OXIDES			
	B <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	P <sub>2</sub> O <sub>5</sub>	SUB TOTAL	TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	ZrO <sub>2</sub>	SUB TOTAL
Composition of Fibers with FeO <sub>3</sub> and MnO additions								
194	--	64.9	--	64.9	--	0.06	--	0.06
195	--	49.8	--	49.8	.01	18.0	.01	18.02
196	--	50.4	--	50.4	.03	7.45	.01	7.49
197	--	64.34	--	64.34	--	0.06	--	0.06
198	--	63.70	--	63.70	--	1.20	--	1.20
199	--	63.54	--	63.54	--	1.20	--	1.20
200	--	38.9	--	38.9	.01	6.70	.01	6.72
201	--	64.3	--	64.3	--	0.06	--	0.06
202	--	44.6	--	44.6	.01	0.92	.01	0.94
203	--	63.3	--	63.3	--	1.15	--	1.15
204	--	63.6	--	63.6	--	0.06	--	0.06
205	--	43.8	--	43.8	.01	15.26	.01	15.28
206	--	62.3	--	62.3	--	1.20	--	1.20
207	--	63.3	--	63.3	--	0.06	--	0.06
208	--	43.9	--	43.9	.01	14.3	.01	14.32
209	--	62.0	--	62.0	--	0.06	--	0.06
210	--	60.0	--	60.0	--	2.0	--	2.0
211	--	60.0	--	60.0	--	--	--	--

SUBSTITUTE SHEET

-26-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	BASIC OXIDES										SUB TOTAL
	FeO <sub>3</sub>	MnO	La <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	MgO	Li <sub>2</sub> O	CaO	BaO	Na <sub>2</sub> O	K <sub>2</sub> O	
Composition of Fibers with FeO <sub>3</sub> and MnO additions											
194	0.06	--	--	--	8.72	--	26.6	--	--	--	35.38
195	.22	--	--	--	0.2	--	31.5	--	--	--	31.92
196	.48	.04	--	--	15.2	--	26.2	--	.07	.05	42.04
197	.50	--	--	--	7.80	--	26.4	--	--	--	34.7
198	.69	--	--	--	7.73	--	25.30	--	--	--	33.72
199	.72	--	--	--	7.70	--	25.04	--	--	--	33.46
200	.80	--	--	--	16.1	--	37.5	--	--	--	54.40
201	.96	--	--	--	8.6	--	26.4	--	--	--	35.96
202	1.02	--	--	--	18.1	--	32.8	--	--	--	51.92
203	1.61	--	--	--	7.98	--	25.4	--	--	--	34.99
204	1.92	--	--	--	8.6	--	26.1	--	--	--	36.62
205	2.90	.04	--	.14	22.7	--	15.05	--	.10	.01	40.94
206	3.05	--	--	--	8.0	--	25.0	--	--	--	36.05
207	3.45	--	--	--	8.0	--	25.5	--	--	--	36.95
208	3.50	--	--	--	24.4	--	13.7	--	--	--	41.6
209	4.81	--	--	--	8.0	--	25.5	--	--	--	38.31
210	--	8.0	--	--	30.0	--	--	--	--	--	38.0
211	--	20.0	--	--	20.0	--	--	--	--	--	40.0

SUBSTITUTE SHEET

-27-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	MISCELLANEOUS			TOTAL
	SO <sub>3</sub>	Misc.	SUB TOTAL	
<u>Composition of Fibers with FeO<sub>3</sub> and MnO additions</u>				
194	--	--	--	100.34
195	.05	.02	.07	99.81
196	.05	.02	.07	100.00
197	--	--	--	99.1
198	--	--	--	98.62
199	--	--	--	98.20
200	.05	.02	.07	100.09
201	--	--	--	100.32
202	--	--	--	97.46
203	--	--	--	99.44
204	--	--	--	100.28
205	.05	.08	.13	100.15
206	--	--	--	99.55
207	--	--	--	100.31
208	--	--	--	99.82
209	--	--	--	100.37
210	--	--	--	100.0
211	--	--	--	100.0

INSTITUTE SHEET

- 28 -

TABLE 3  
COMPOSITION OF FIBERS

TEST NO.	ACIDIC OXIDES			AMPHOTERIC OXIDES			SUB TOTAL
	B <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	P <sub>2</sub> O <sub>5</sub>	TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	ZrO <sub>2</sub>	
<u>Composition of Fibers with La<sub>2</sub>O<sub>3</sub> additions</u>							
--	--	58.1	--	--	0.06	--	0.06
213	--	57.8	--	--	0.06	--	0.06
214	--	57.5	--	--	0.06	--	0.06
215	--	56.9	--	--	0.06	--	0.06
<u>Composition of Fibers with Cr<sub>2</sub>O<sub>3</sub> additions</u>							
216	--	62.6	--	0.01	0.49	0.01	0.51
<u>Composition of Fibers with Na<sub>2</sub>O additions</u>							
17	--	64.7	--	--	0.06	--	0.06
218	--	64.5	--	--	0.06	--	0.06
219	--	64.4	--	--	0.06	--	0.06
220	--	63.5	--	--	1.20	--	1.20
221	--	64.3	--	--	0.06	--	0.06
222	--	64.2	--	--	0.06	--	0.06
223	--	64.0	--	--	0.06	--	0.06
224	--	63.0	--	--	0.06	--	0.06
225	--	60.3	--	--	0.06	--	0.06

SUBSTITUTE SHEET

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	BASIC OXIDES										SUB TOTAL
	FeO <sub>3</sub>	MnO	La <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	MgO	Li <sub>2</sub> O	CaO	BaO	Na <sub>2</sub> O	K <sub>2</sub> O	
<u>Composition of Fibers with La<sub>2</sub>O<sub>3</sub> additions</u>											
--	0.16	--	0.00	--	4.60	--	36.71	--	--	--	41.47
213	0.15	--	0.56	--	4.58	--	36.53	--	--	--	41.82
214	0.15	--	0.72	--	4.55	--	36.3	--	--	--	41.72
215	0.15	--	0.92	--	4.51	--	36.0	--	--	--	41.58
<u>Composition of Fibers with Cr<sub>2</sub>O<sub>3</sub> additions</u>											
216	0.08	.00	--	0.09	2.30	--	34.10	0.00	0.03	0.01	36.61
<u>Composition of Fibers with Na<sub>2</sub>O additions</u>											
17	--	--	--	--	8.7	--	26.6	--	0.28	--	35.58
218	--	--	--	--	8.7	--	26.5	--	0.45	--	35.65
219	--	--	--	--	8.6	--	26.5	--	0.71	--	35.80
220	--	--	--	--	8.5	--	26.1	--	0.87	--	35.70
221	--	--	--	--	8.5	--	26.2	--	0.93	--	35.63
222	--	--	--	--	8.6	--	26.4	--	1.11	--	36.11
223	--	--	--	--	8.6	--	26.3	--	1.40	--	36.3
224	--	--	--	--	8.5	--	25.9	--	2.60	--	37.0
225	--	--	--	--	8.1	--	24.8	--	6.84	--	39.74

-30-

TABLE 3  
COMPOSITION OF FIBERS (continued)

TEST NO.	MISCELLANEOUS			TOTAL
	SO <sub>3</sub>	Misc.	SUB TOTAL	
<u>Composition of Fibers with La<sub>2</sub> O<sub>3</sub> additions</u>				
--	--	--	--	99.63
213	--	--	--	99.68
214	--	--	--	99.28
215	--	--	--	98.54
<u>Composition of Fibers with Cr<sub>2</sub>O<sub>3</sub> additions</u>				
216	--	--	--	99.72
<u>Composition of Fibers with Na<sub>2</sub>O additions</u>				
17	--	--	--	100.34
218	--	--	--	100.21
219	--	--	--	100.26
220	--	--	--	100.40
221	--	--	--	99.99
222	--	--	--	100.37
223	--	--	--	100.36
224	--	--	--	100.06
225	--	--	--	100.1

SUBSTITUTE SHEET



TABLE 3  
COMPOSITION OF FIBERS

TEST NO.	ACIDIC OXIDES			AMPHOTERIC OXIDES				
	B <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	P <sub>2</sub> O <sub>5</sub>	SUB TOTAL	TiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	ZrO <sub>2</sub>	SUB TOTAL
Composition of Conventional Mineral Wools								
226	-	40.0	-	40.0	0.37	9.1	0.03	9.50
	-	39.9	0.02	39.92	1.11	12.85	0.03	13.99
228	-	37.65	0.84	38.49	2.35	9.85	0.04	12.24
229	-	41.75	0.12	41.87	1.07	16.0	0.03	17.10

Composition of Refractory Fibers (Fibers with less than 25% Basic Oxides)

231	-	31.0	-	-	47.5	0.02		47.52
232	-	37.1	-	-	59.2	-		59.2
233	-	50.0	-	-	40.0	-		40.0
234	-	54.0	-	-	46.0	-		46.0
235	-	58.47	1.15	0.98	24.54	0.03		25.55
236	-	52.1	-	1.76	44.4	.23		46.39
237	-	52.0	-	1.71	42.2	2.93		46.84
238	-	49.8	-	1.60	38.3	9.32		49.22
239	-	48.6	-	1.55	36.2	12.3		50.05
240	-	47.8	-	1.50	34.4	15.1		51.00
241	-	46.2	-	1.40	31.0	20.7		53.10
242	-	28	-	19	50	3		72
243	-	64.5	-	-	27.4	-		27.4

SUBSTITUTE SHEET

- 32 -

TABLE 3 (cont'd.)  
COMPOSITION OF FIBERS

TEST	BASIC OXIDES										MISCELLANEOUS					
	NO.	FeO <sub>3</sub>	MnO	La <sub>2</sub> O <sub>3</sub>	Cr <sub>2</sub> O <sub>3</sub>	MgO	Li <sub>2</sub> O	CaO	BaO	Na <sub>2</sub> O	K <sub>2</sub> O	SUB TOTAL	SO <sub>3</sub>	Misc.	SUB TOTAL	TOTAL
Composition of Conventional Mineral Wools																
226	0.47	0.64	-	0.02	0.02	11.2	0.01	36.5	0.04	0.54	0.55	49.97	0.1	0.59	0.69	100.16
	0.35	0.24	-	0.00	0.00	6.05	0.01	38.55	0.12	0.23	0.27	45.82	0.67	0.07	0.74	100.47
228	9.7	0.22	-	0.04	0.04	12.95	0.01	23.55	0.07	2.01	0.80	49.35	0.42	0.19	0.61	100.69
229	3.75	0.23	-	0.02	0.02	6.45	0.63	27.75	0.03	2.04	0.63	41.53	0.56	0.08	0.64	101.14

Composition of Refractory Fibers (Fibers with less than 25% Basic Oxides)

231	-	-	-	-	-	-	-	1.2	-	20.2	-	21.4	-	-	-	99.92
232	-	-	-	-	-	-	-	0.2	-	3.1	-	3.3	-	-	-	99.6
233	-	-	-	-	-	-	-	5.6	-	4.4	-	10.0	-	-	-	100
234	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	100
235	3.70	0.02	-	0.00	0.00	1.44	0.02	5.78	0.54	1.55	1.18	14.23	0.47	0.24	0.71	100.11
236	.83	-	-	-	-	0.07	-	0.12	-	.05	.06	1.13	-	-	-	99.62
237	.77	-	-	-	-	0.07	-	0.12	-	.05	.06	1.07	-	-	-	99.91
238	.72	-	-	-	-	0.07	-	0.12	-	.05	.06	1.02	-	-	-	100.04
239	.70	-	-	-	-	0.07	-	0.12	-	.05	.06	1.00	-	-	-	99.65
240	.68	-	-	-	-	0.07	-	0.12	-	.05	.06	.98	-	-	-	99.78
241	.63	-	-	-	-	0.07	-	0.12	-	.05	.06	0.93	-	-	-	100.23
242	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	100
243	-	-	-	-	-	-	8.4	-	-	-	-	8.4	-	-	-	100.3

SUBSTITUTE SHEET

- 33 -

TABLE 4  
TEST RESULTS ON FIBERS MADE WITH ALUMINA ADDITIONS

COMPOSITION, WT%										5 Hour		
Acidic Oxides		Amphoteric Oxides		Basic Oxides				Total Analytical		Saline Extraction	E-119 Fire Test	
No.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total	CaO	MgO	Total				ppm. Si	Thickness	2 Hour Test**
0 to 1 1/2% Amphoteric Oxides												
1	32	0.2	0.22	39	29	68.1		100.37		*	*	*
2	31.3	0.2	0.22	33.3	35.5	68.9		100.47		*	*	*
3	41.9	0.28	0.30	57.5	0.1	57.7		99.95		80	-	-
4	43.5	0.33	0.35	46.0	10.4	56.5		100.40		58	-	-
5	43.7	0.25	0.27	39.8	16.6	56.5		100.52		46	2.0/1.27	F
6	45.0	0.50	0.52	54.4	0.1	54.6		100.17		75	-	-
7	46.5	0.20	0.22	9.2	45.1	54.4		101.17		*	*	*
8	48.2	0.20	0.22	5.0	47.6	52.7		101.17		*	*	*
9	47.9	0.22	0.24	19.3	33.5	52.9		101.09		50	-	-
10	48.5	0.56	0.58	8.8	43.0	51.9		101.03		51	-	-
11	48.6	0.56	0.58	13.3	38.3	51.7		100.93		46	-	-
12	49.2	0.42	0.44	28.0	22.9	51.0		100.69		67	-	-
13	49.2	0.17	0.19	3.4	48.3	51.8		101.24		*	*	*
14	50.0	0.10	0.12	7.0	43.0	50.1		100.27		56	-	-
15	50.7	0.10	0.12	15.7	33.7	49.5		100.37		60	-	-
16	51.1	0.45	0.47	29.8	19.0	48.9		100.52		65	-	-
17	51.2	0.33	0.35	39.7	9.0	48.8		100.40		51	2.0/2.59	F
18	53.2	0.64	0.66	2.8	44.3	47.2		101.11		56	-	F
19	53.4	0.28	0.30	45.6	0.1	45.8		99.55		77	2.0/1.97	F

\* = Not Fiberizable

\*\* P = Pass, F = Failed

SUBSTITUTE SHEET

-34-

EXPERIMENTAL DATA

<u>COMPOSITION, WT%</u>										5 Hour		
Acidic Oxides		Amphoteric Oxides		Basic Oxides		Total Analytical				Saline Extraction	E-119 Fire Test	2 Hour Test**
NO.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total	CaO	MgO	Total	Total	Total	Total	ppm. Si	Thickness	Density
<u>0 to 1 1/2% Amphoteric Oxides</u>												
20	53.8	0.33	0.35	35.1	10.8	46.0	100.20	83	2.0/1.97	F		
21	53.9	0.40	0.42	25.5	20.5	46.1	100.47	68				
22	54.5	1.00	1.02	7.5	36.5	44.1	99.67	30				
23	55.9	0.08	0.10	43.0	0.45	43.55	99.60	51	2.0/1.94	F		
24	56.0	0.40	0.42	27.0	17.0	44.1	100.57	69	2.0/2.12	F		
25	56.35	0.20	0.24	34.4	8.25	42.75	99.39	70	2.0/1.87	F		
26	56.4	0.91	0.93	35.1	7.39	42.59	99.97	47				
27	57.0	1.03	1.05	24.5	17.6	42.2	100.30	46				
28	57.0	1.09	1.11	35.0	6.84	41.94	100.10	40				
29	57.25	0.92	0.94	36.95	3.95	41.1	99.56	56	1.88/2.20	F		
30	57.8	0.75	0.78	34.75	6.2	41.05	99.85		2.0 / 1.97	F		
31	58.1	0.03	0.05	36.7	4.53	41.33	99.53	59	2.0 / 1.91	F		
32	58.2	1.08	1.10	35.7	4.79	40.59	99.94	80	2.0 / 1.91	F		
33	58.3	0.03	0.05	40.8	0.31	41.21	99.61	49	2.0 / 1.91	F		
34	58.4	0.37	0.39	15.3	26.3	41.7	100.54	61	2.0 / 1.91	F		
35	58.6	0.09	0.11	35.0	5.36	40.46	99.22	74	2.0 / 1.94	P		
36	58.7	0.05	0.07	40.2	0.27	40.57	99.39	58	2.0 / 1.91	F		
37	58.5	0.49	0.53	34.4	5.6	40.1	99.32	59	2.0 / 2.01	P		
38	58.8	0.41	0.43	35.4	6.2	41.7	100.98	56				

\* = Not Fiberizable

\*\* P = Poor, F = Failed

SUBSTITUTE SHEET

-35-

EXPERIMENTAL DATA

COMPOSITION, WT%										5 Hour		
Acidic Oxides		Amphoteric Oxides		Basic Oxides			Total Analytical	Extraction ppm. Si	E-119 Fire Test			
NO.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total	CaO	MgO	Total			Thickness	2 Hour Test**		
0 to 1 1/2% Amphoteric Oxides												
39	58.9	0.08	0.10	34.2	6.10	40.4	99.45	67	2.0/1.86	P		
40	59.0	0.24	0.26	35.9	3.8	39.9	99.21	49	2.0/1.97	P		
41	59.1	0.09	0.11	40.3	0.43	40.83	100.09	68	2.0/1.90	P		
42	59.2	0.24	0.26	4.7	36.8	41.60	101.11	47	2.5/1.4	F		
43	59.15	0.32	0.34	35.55	4.75	40.40	99.94	60	2.0/1.95	P		
44	59.4	0.04	0.06	29.8	10.7	40.60	100.11	61	2.0/1.92	P		
45	59.5	0.02	0.04	34.2	5.98	40.28	99.87	77	2.0/1.90	P		
46	59.5	0.02	0.04	32.1	8.16	40.36	99.95	73	2.0/1.89	F		
47	59.6	1.43	1.45	22.5	16.8	39.6	100.8	51	2.0/1.88	F		
48	59.6	0.03	0.05	28.7	11.4	40.2	99.9	70	2.0/1.91	P		
50	59.8	0.28	0.30	40.5	0.11	40.71	100.86	30	2.0/2.01	P		
51	59.9	1.48	1.50	25.8	12.9	39.0	100.55	47	2.0/1.98	P		
52	59.9	1.31	1.33	28.1	11.0	39.4	100.78	45	2.0/1.95	P		
53	60.0	1.41	1.43	22.3	16.4	39.0	100.58	41	2.0/1.91	P		
54	60.3	0.17	0.19	32.3	6.36	38.76	99.30	59	2.0/1.89	P		
55	60.4	1.05	1.07	28.5	9.85	38.45	99.97	45	2.0/1.95	P		
56	60.5	1.11	1.13	27.9	10.7	38.9	100.68	36	2.0/1.94	F		
57	60.7	0.93	0.95	28.7	9.47	38.27	99.97	51	2.0/1.93	P		
58	60.8	0.2	0.22	36.	3.	39.10	100.17	56				

\* = Not Fiberizable

\*\* P = Poor, F = Failed

SUBSTITUTE SHEET

-36-

EXPERIMENTAL DATA

COMPOSITION, WT%										5 Hour		
Acidic Oxides		Amphoteric Oxides		Basic Oxides			Total Analytical	Saline Extraction ppm. Si	E-119 Fire Test			
NO.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total	CaO	MgO	Total			Thickness	2 Hour Test**		
0 to 1 1/2% Amphoteric Oxides												
59	61.7	0.02	0.04	32.6	5.19	37.89	99.68	65	2.0/1.97	P		
60	62.4	0.04	0.06	21.7	15.5	37.3	99.81	76	2.0/1.88	P		
61	62.5	0.02	0.04	30.3	6.64	37.04	99.63	66	2.0/1.92	P		
62	62.5	0.03	0.05	29.5	7.70	37.30	99.90	64	2.0/1.82	P		
63	63.1	0.02	0.04	31.1	5.28	36.48	99.67	46	2.0/1.95	P		
64	63.1	1.25	1.27	25.2	10.2	35.5	99.92	19	2.0/1.96	P		
65	63.5	1.49	1.51	24.0	10.9	35.0	100.06	12	2.0/1.91	P		
66	63.8	1.13	1.15	28.4	5.79	34.29	99.29	52	2.0/2.01	P		
67	63.8	1.41	1.43	22.8	11.8	34.7	99.98	17	2.0/1.88	P		
68	64.1	1.23	1.25	30.97	2.60	33.67	99.07	7	2.0/1.88	P		
69	64.1	1.47	1.49	28.6	4.83	33.53	99.17	49	2.0/1.99	P		
70	65.3	0.03	0.05	27.4	6.68	34.18	99.58	37	2.0/1.91	P		
71	65.4	1.15	1.17	3.12	30.1	33.32	99.94	46	2.0/1.88	F		
72	65.6	0.01	0.03	27.4	6.50	34.0	99.68	35	2.0/2.00	P		
73	65.8	0.02	0.04	28.6	5.21	33.91	99.80	44	—	—		
74	65.9	0.03	0.05	21.9	11.8	33.8	99.80	30	2.0/1.87	P		
75	65.9	0.03	0.05	25.8	7.88	33.78	99.78	25	2.0/1.91	P		
76	65.4	1.15	1.17	3.12	30.1	33.23	99.84	46	2.0/1.88	F		

\* = Not Fiberizable

\*\* P = Poor, F = Failed

SUBSTITUTE SHEET

-37-

EXPERIMENTAL DATA

<u>COMPOSITION, WT%</u>									
<u>Acidic Oxides</u>		<u>Amphoteric Oxides</u>		<u>Basic Oxides</u>			<u>5 Hour Saline Extraction</u>		
<u>NO.</u>	<u>SiO<sub>2</sub></u>	<u>Al<sub>2</sub>O<sub>3</sub></u>	<u>Total</u>	<u>CaO</u>	<u>MgO</u>	<u>Total</u>			
<u>0 to 1 1/2% Amphoteric Oxides (Cont.)</u>							<u>ppm. Si</u>		<u>E-119 Fire Test</u>
							<u>Thickess</u>		<u>2 Hour Test**</u>
							<u>Density</u>		
77	66.1	0.59	0.61	4.02	28.7	33.02	50	-	F
78	67.1	-	-	6.43	26.5	33.03	78	2.0/1.89	F
79	67.2	0.02	0.04	8.67	24.0	32.77	84	2.0/2.03	F
80	68.4	-	-	1.6	30.1	31.8	*	*	*
81	68.6	0.25	0.27	29.0	1.09	30.19	18	2.0/2.00	P
82	68.8	-	-	10.2	21.3	31.6	31	-	-
83	68.9	0.03	0.05	18.1	12.7	30.9	30	2.0/2.00	P
84	69.0			7.2	23.8	31.0	18	-	-
<u>1 1/2% to 3% Amphoteric Oxides</u>									
85	50.0	2.00	2.02	5.0	43.0	48.1	-	*	*
86	52.6	2.00	2.02	3.8	41.7	45.6	51	2.0/1.88	F
87	56.1	2.41	2.43	30.3	10.6	41.0	39	2.0/1.89	F
88	56.2	1.82	1.84	24.4	17.3	41.8	65	-	-
89	58.1	2.01	2.03	3.83	36.3	40.43	44	2.0/1.99	P
90	58.9	2.26	2.28	36.6	1.4	38.1	18	2.0/1.82	P
91	59.0	2.93	2.95	36.3	1.0	37.4	9	2.0/1.87	P
92	59.4	0.38	2.69	34.9	2.1	37.1	25	2.0/2.06	P
93	59.8	2.54	2.56	27.4	10.0	37.5	11	-	-
94	60.1	1.68	1.70	28.0	9.9	38.0	29	2.0/1.98	P

\* = Not Fiberizable

\* P = Pass, F = Failed

SUBSTITUTE SHEET

EXPERIMENTAL DATA

<u>COMPOSITION, WT%</u>										<u>5 Hour</u>		
<u>Acidic</u>		<u>Amphoteric</u>		<u>Oxides</u>		<u>Basic Oxides</u>		<u>Total</u>		<u>Saline</u>		
<u>No.</u>	<u>SiO<sub>2</sub></u>	<u>Al<sub>2</sub>O<sub>3</sub></u>	<u>Total</u>	<u>CaO</u>	<u>MgO</u>	<u>Total</u>	<u>Total</u>	<u>Analytical</u>	<u>Extraction</u>	<u>ppm. Si</u>	<u>Thickness</u>	<u>2 Hour</u>
<u>1 1/2% to 3% Amphoteric Oxides (Cont.)</u>										<u>Density</u>	<u>Test**</u>	
95	60.2	2.21	2.23	32.7	4.9	37.7	100.18	50	50	2.0/2.04	P	
96	61.4	2.17	2.19	26.2	10.1	36.4	100.04	18	18	2.0/1.87	P	
97	61.4	1.66	1.68	29.9	6.9	36.9	100.03	61	61	2.0/1.91	P	
98	61.8	2.84	2.86	34.0	0.2	34.3	99.01	51	51	2.0/1.93	P	
99	62.0	2.81	2.83	34.1	0.2	34.4	99.28	55	55	2.0/1.90	P	
100	62.1	2.75	2.77	33.8	0.2	34.1	99.02	13	13	2.0/1.91	P	
101	62.7	1.79	1.81	25.6	9.4	35.1	99.66	18	18	2.0/1.96	P	
102	63.0	2.54	2.56	33.1	0.2	33.4	99.05	37	37	2.0/1.87	P	
103	63.9	1.84	1.86	30.7	2.5	33.3	99.11	38	38	2.0/1.94	P	
104	64.1	1.83	1.85	17.7	16.3	34.3	100.4	12	12	2.0/1.95	P	
105	65.1	2.15	2.17	9.74	23.1	33.15	100.57	17	17	-	P	
106	65.6	1.56	1.58	2.7	29.7	32.5	99.73	33	33	2.0/1.91	P	
107	66.7	1.80	1.82	30.7	0.1	30.9	99.47	2	2	2.0/1.90	P	

3 to 4% Amphoteric Oxides

108	49.8	3.5	3.52	4.98	40.9	46.18	99.65	33	-	-	-	
109	50.3	3.58	3.60	45.0	0.64	45.74	99.69	19	19	2.0/1.96	F	
110	55.1	3.77	3.79	7.89	33.7	41.89	100.93	33	33	2.0/2.06	P	

\* = Not Fiberizable

\*\* P = Pass, F = Failed

SUBSTITUTE SHEET



-39-

EXPERIMENTAL DATA

COMPOSITION, WT%									
Acidic		Amphoteric		Basic Oxides			Total	5 Hour	
Oxides		Oxides		CaO	MgO	Total		Extraction	Saline
NO.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total	CaO	MgO	Total	Analytical	ppm. Si	E-119 Fire Test
3% to 4% Amphoteric Oxides (Cont.)									
111	55.6	0.24	3.66	37.1	4.65	41.85	101.16	-	2.0/2.12 F
112	56.5	0.35	3.65	36.51	4.17	40.78	100.98	-	2.0/1.99 F
113	56.7	3.52	3.54	23.5	16.2	39.8	100.09	19	2.0/1.89 F
114	56.7	3.06	3.08	23.4	16.6	40.28	100.11	40	2.0/4.02 F
115	56.88	0.32	3.64	36.45	4.00	40.45	101.02	51	- F
115a	57.5	3.29	3.31	37.7	0.75	38.55	99.41	6	2.0/1.93 F
116	58.1	3.05	3.07	25.6	12.8	38.5	99.72	20	2.0/1.9 F
117	58.2	3.75	3.77	36.4	0.67	37.17	99.19	38	2.0/2.0 F
119	58.80	3.76	3.78	36.7	0.24	37.04	99.67	28	2.0/1.97 F
120	61.2	3.77	3.79	34.0	0.24	34.34	99.38	18	2.0/1.94 P
4 to 6% Amphoteric Oxides									
121	49.7	4.04	4.06	26.4	19.6	46.1	99.91	37	- F
122	55.8	5.20	5.22	30.1	9.2	39.4	100.47	7	2.0/1.88 F
123	56.85	5.40	5.41	31.8	5.65	37.55	99.91	4	2.0/1.99 F
124	57.0	4.68	4.70	22.0	15.6	37.7	99.45	32	2.0/2.00 F

\* = Not Fiberizable

\*\* P = Pass, F = Failed

\* = Not Fiberizable

\*\* P = Pass, F = Failed

SUBSTITUTE SHEET

-40-

EXPERIMENTAL DATA

<u>COMPOSITION, WT%</u>										5 Hour		
Acidic		Amphoteric								Saline	E-119 Fire Test	
<u>Oxides</u>		<u>Oxides</u>		<u>Basic Oxides</u>						<u>Extraction</u>	<u>Thickness</u>	<u>2 Hour</u>
<u>NO.</u>	<u>SiO<sub>2</sub></u>	<u>Al<sub>2</sub>O<sub>3</sub></u>	<u>Total</u>	<u>CaO</u>	<u>MgO</u>	<u>Total</u>	<u>Total</u>	<u>Analytical</u>	<u>ppm. Si</u>		<u>Density</u>	<u>Test**</u>
<u>6 to 8% Amphoteric Oxides</u>												
125	39.2	6.90	6.92	38.5	14.0	52.6	98.72		37	-	-	-
126	46.9	7.66	7.68	44.8	0.3	45.2	99.83		6		2.0/1.97	F
127	49.3	6.40	6.42	25.3	18.4	43.8	99.57		19		2.0/2.0	F
128	50.4	7.45	7.48	26.2	15.2	41.5	99.43		18		2.0/3.17	F
129	54.7	7.60	7.62	30.7	6.5	37.3	99.67		7		2.0/1.98	F
130	56.1	6.34	6.36	30.6	6.9	37.6	100.11		4		2.0/2.04	F
131	57.9	6.7	6.72	5.9	29.7	35.6	100.27		2		-	-
132	58.5	6.16	6.18	31.2	4.0	35.2	99.93		2		2.0/2.01	F
133	59.7	7.08	7.10	27.9	5.1	33.1	99.9		2		2.0/2.04	F
<u>8 to 10% Amphoteric Oxides</u>												
134	38.6	9.3	9.32	38.4	13.7	52.2	100.17		12		-	-
135	42.8	8.8	9.13	36.7	9.6	46.76	98.69		13		-	-
136	44.5	8.76	8.78	45.5	0.52	46.12	99.45		3		-	-
137	52.1	8.9	8.92	23.7	16.2	40.0	101.02		1.2		-	-
138	52.5	9.67	9.69	33.5	4.21	37.81	100.05		1.0		2.0/1.99	F
139	53.7	8.7	8.72	22.5	16.3	38.9	101.37		1.7		-	-
140	56.6	9.2	9.22	23.5	10.9	34.5	100.37		1.2		2.0/2.05	F

\* = Not Fiberizable

\*\* P = Pass, F = Failed

SUBSTITUTE SHEET

EXPERIMENTAL DATA

COMPOSITION, WT%														
Acidic		Amphoteric		Basic Oxides						Total Analytical	5 Hour Saline		E-119 Fire Test	
Oxides		Oxides		CaO	MgO	Total	Extraction	Thicknss	2 Hour					
NO.	SiO <sub>2</sub>	Al <sub>2</sub> O <sub>3</sub>	Total				ppm. Si	Density	Test**					
10 to 12% Amphoteric Oxides														
141	41.0	10.05	10.07	48.25	0.3	48.70	6	2.0/2.00	F					
142	51.3	10.9	10.92	37.2	0.2	37.5	0.8	2.0/2.04	F					
143	52.4	10.7	10.72	23.1	16.1	39.3	0.7	2.0/2.00	F					
144	52.7	10.2	10.22	22.1	16.0	38.2	0.5	-	-					
22 to 20% Amphoteric Oxides														
145	41.5	13.0	13.02	44.2	0.5	44.8	1.2	-	-					
146	49.8	18.0	18.02	31.5	0.2	32.02	0.5	-	-					
147	55.6	12.9	12.92	13.2	18.4	31.7	1.8	2.0/2.54	F					
20 to 30% Amphoteric Oxides														
148	36.5	28.4	28.42	34.4	0.3	34.8	0.6	-	-					
149	40.3	21.5	21.52	37.5	0.3	37.9	0.8	-	-					
150	42.6	25.7	25.72	31.2	0.3	31.6	0.6	-	-					
151	48.4	22.4	22.42	16.5	12.6	29.2	0.5	2.0/2.01	F					
152	59.9	22.8	22.82	3.1	14.0	17.2	0.7	2.0/2.01	F					
30 to 40% Amphoteric Oxides														
153	45.9	31.3	31.32	5.9	16.7	22.7	2.3		-					

154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

-41-

\*\* P = Pass, F = Failed

\* = Not Fiberizable

-42-

TABLE 5  
FIBERS MADE WITH VARIOUS ADDITIVE CONSTITUENTS

<u>ANALYSES</u>									
5 Hour									
		Saline		E-119 Fire Test					
Acidic	Amphoteric	Basic	% Additive	Extraction	Thickness	2 Hour			
NO. Oxides	Oxides	Oxides	Total (Incl.Total)	ppm. Si	Density	Test			
<u>Fibers with B<sub>2</sub>O<sub>3</sub> Additions</u>									
164	65.12	0.06	35.3	-	100.48	0.32% B <sub>2</sub> O <sub>3</sub>	53	2.0/1.94	P
165	64.42	1.20	34.8	-	100.42	0.52%	20	2.0/1.88	P
166	65.24	0.06	35.2	-	100.5	0.64%	43	2.0/1.89	P
167	65.32	0.06	35.2	-	100.58	0.82%	45	2.0/2.00	P
168	65.43	0.06	34.9	-	100.39	1.33%	47	2.0/1.95	P
169	65.47	0.06	34.9	-	100.43	1.37%	45	2.0/ -	P
170	65.82	0.06	34.6	-	100.48	2.22%	46	2.0/2.02	P
171	68.01	0.06	32.0	-	100.07	8.41%	52	2.0/6.45	P
<u>Fibers with P<sub>2</sub>O<sub>5</sub> addition</u>									
172	55.65	0.48	43.58	0.02	99.7	6.06% P <sub>2</sub> O <sub>5</sub>	71	2.0/1.94	F
<u>Fibers with TiO<sub>2</sub> addition</u>									
173	48.6	51.4	-	-	100.	10% TiO <sub>2</sub>	0.4	2.01/1.94	P

SUBSTITUTE SHEET

-43-

ANALYSES									
NO.	Acidic Oxides	Amphoteric Oxides	Basic Oxides	Misc.	Total	% Additive (Incl.Total)	Extraction	5 Hour	
								Saline	E-119 Fire Test
								ppm. Si	Thickness Density Test
<u>Fibers with ZrO<sub>2</sub> additions</u>									
174	63.5	1.10	35.92	-	100.52	0.21% ZrO <sub>2</sub>	25		2.0/2.01 P
175	59.2	0.73	39.51	-	99.44	0.40%	48		2.0/2.00 P
176	59.5	0.73	39.52	-	99.75	0.42%	55		- -
177	59.7	0.84	39.16	-	99.70	0.50%	32		- -
178	60.0	0.90	38.78	-	99.68	0.54%	40		- -
179	59.2	0.93	37.98	-	98.11	0.58%	46		2.0/2.02 P
180	54.3	1.88	43.12	.01	99.31	0.58%	67		2.0/2.00 F
181	59.2	1.15	37.73	-	98.08	0.83%	57		2.0/2.03 P
182	46.85	2.89	49.98	.02	99.74	0.84%	44		2.0/2.17 F
182a	59.4	2.69	36.96	.02	99.05	2.31%	25		2.0/2.00 P
183	59.05	2.95	38.07	-	100.09	2.65%	38		2.0/2.20 P
184	57.96	3.53	38.72	-	100.21	3.11%	25		2.0/2.37 F
185	57.80	3.68	38.14	-	99.62	3.12%	10		2.0/2.03 F
186	59.05	3.65	39.51	-	102.21	3.27%	15		2.1/2.11 P
187	56.88	3.62	40.45	-	100.95	3.30%	51		- -
188	57.7	3.50	39.0	-	100.20	3.30%	13		2.0/2.06 P
189	58.19	3.75	38.65	-	100.59	3.36%	12		- -
190	57.86	3.73	38.88	-	100.47	3.37%	-		2.0/2.00 F
191	58.6	4.25	36.22	-	99.07	3.67%	7		2.0/2.00 P
192	58.4	4.34	35.79	-	98.53	3.69%	3		2.0/2.00 P
193	58.65	7.87	35.36	.01	99.89	4.50%	1.3		2.0/2.07 F

SUBSTITUTE SHEET

-44-

## ANALYSES

ANALYSES												
		5 Hour										
		Saline		E-119 Fire Test								
		Extraction		Thickess		2 Hour						
		ppm. Si		Density		Test						

SUBSTITUTE SHEET

ANALYSES

ANALYSES									
Test No.	Acidic Oxides	Amphoteric Oxides	Basic Oxides	Misc.	Total	% Additive (Incl.Total)	5 Hour		
							Saline Extraction	E-119 Fire Test Thickness	2 Hour Test
Fibers with La <sub>2</sub> O <sub>3</sub> additions									
212	58.1	0.06	41.47	-	99.63	0.00% La <sub>2</sub> O <sub>3</sub>	76	2.0/1.97	F
213	57.8	0.06	41.82	-	99.68	0.56% "	69	2.0/1.97	F
214	57.5	0.06	41.72	-	99.28	0.72% "	78	2.0/1.98	F
215	56.9	0.06	41.58	-	99.54	0.92% "	70	2.0/1.98	F
Fibers with Cr <sub>2</sub> O <sub>3</sub> additions									
216	62.6	0.51	36.61	-	99.72	0.09% Cr <sub>2</sub> O <sub>3</sub>	28	2.0/2.16	P
Fibers with Na <sub>2</sub> O additions									
217	64.7	0.06	35.58	-	100.34	0.28% Na <sub>2</sub> O	45	2.0/1.91	P
218	64.5	0.06	35.68	-	100.21	0.45% "	57	2.0/1.97	P
219	64.4	0.06	35.80	-	100.26	0.71% "	54	2.0/1.97	P
220	63.5	1.20	35.70	-	100.40	0.87% "	30	2.0/1.90	P
221	64.3	0.06	35.63	-	99.99	0.93% "	51	2.0/1.90	P
222	64.2	0.06	36.11	-	100.37	1.11% "	57	2.0/1.99	P
223	64.0	0.06	36.3	-	100.36	1.40% "	43	2.0/1.99	P
224	63.0	0.06	37.0	-	100.06	2.60% "	50	2.0/2.16	F
225	60.3	0.06	39.74	-	100.1	6.84% "	70	2.0/1.87	F

- 45 -

SUBSTITUTE SHEET

ANALYSES

<u>ANALYSES</u>										
Test	Acidic	Amphoteric	Basic	% Additive			5 Hour		E-119 Fire Test	
				Oxides	Oxides	Oxides	Extraction	Saline	Thickness	2 Hour
<u>Conventional Mineral Wool Fibers</u>										
226	40.0	9.50	49.97	0.69	100.16	-	7	2.0/3.50		F
227	39.92	13.99	45.82	0.74	100.47	-	1.2	2.0/5.23		F
228	38.49	12.24	49.35	0.61	100.69	-	0.6	2.0/3.42		F
229	41.87	17.10	41.53	0.64	101.14	-	1.0	2.0/3.86		F

Refractory Fibers - (Fibers with less than 25% Basic Oxides)

231	31.0	47.52	21.4	-	99.92	-	-	2	2.0/2.10	F	F
232	37.1	59.2	3.3	-	99.6	-	-	0.6	2.0/5.38	F	F
233	50.0	40.0	10.0	-	100	-	-	0.8	2.0/2.00	P	P
234	54.0	46.0	-	-	100	-	-	0.3	2.0/2.00	P	P
235	59.62	25.55	14.23	0.7	100.11	-	-	0.3	2.0/2.00	P	P
236	52.1	46.39	1.13	-	99.62	-	-	1.0	-	-	-
237	52.0	46.84	1.07	-	99.91	-	-	0.4	-	-	-
238	49.8	49.22	1.02	-	100.04	-	-	0.3	-	-	-
239	48.6	50.05	1.00	-	99.65	-	-	0.4	-	-	-
240	47.8	51.00	0.98	-	99.78	-	-	0.3	-	-	-
241	46.2	53.10	0.93	-	100.23	-	-	0.4	-	-	-
242	28	72	-	-	100	-	-	0.5	-	-	-
243	64.5	27.4	8.4	-	100.3	-	-	0.8	2.0/1.85	F	F

SUBSTITUTE SHEET



-47-

TABLE 6

CONTINUOUS SERVICE TEMPERATURE  
FOR CONSTANT  $\text{SiO}_2/\text{CaO}/\text{MgO}$  RATIOS

<u><math>\text{SiO}_2/\text{CaO}/\text{MgO}</math> Ratio</u>	<u>Continuous Service Temperature for max 5% shrinkage</u>			
	<u>0</u>	<u>5</u>	<u>10</u>	<u>30</u>
	°F			
50/50/0	1480	1480	1470	1550
50/40/10	1440	1430	1420	1520
50/30/10	1400	1380	1370	1480
60/40/0	1500	1460	1460	1600
60/30/10	1430	1420	1400	1520
60/20/20	1380	1370	1360	1500

SUBSTITUTE SHEET

-48-

Reasonable modifications and variations are possible from the foregoing disclosure without departing from either the spirit or scope of the invention as defined in the claims.

**SUBSTITUTE SHEET**

-49-

CLAIMS

1. A process for decomposing a silica-containing fiber comprising the steps of:

1. providing an inorganic fiber prepared from a composition consisting essentially of:

(a) 0.06-10 wt% of a material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 35-70 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

(d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight;

2. subjecting the silica-containing fiber to a physiological saline fluid; and

3. extracting the silica at a rate of at least 5 parts per million (ppm) of silicon in 5 hours, thereby decomposing the silica-containing fiber.

2. The process of Claim 1 wherein the composition of subsection 1(a) ranges from 0.06-5 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof.

3. The process of Claim 1 wherein the composition of subsection 1(c) ranges from 0.25-50 wt%  $\text{MgO}$ .

4. The process of Claim 1 wherein the composition consists essentially of:

SUBSTITUTE SHEET

-50-

(a) 0.06-1.5 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-70 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

(d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight.

5  
10 5. The process of Claim 4 wherein the composition in subsection 1(c) ranges from 0.25-50 wt%  $\text{MgO}$ .

6. The process of Claim 1 wherein the composition consists essentially of:

15 (a) 1.5-3 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-66 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

20 (d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight.

7. The process of Claim 1 wherein the composition of subsection 1(c) ranges from 0.25-50 wt%  $\text{MgO}$ .

25 8. The process of Claim 1 wherein the composition consists essentially of:

(a) 3-4 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-63 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

**SUBSTITUTE SHEET**

-51-

(d) the remainder consisting essentially of CaO, the total being 100% by weight.

5           9. The process of Claim 8 wherein the composition of subsection 1(c) ranges from 0.25-50 wt% MgO.

10           10. The process of Claim 1 wherein the composition consists essentially of:

- 10           (a) 4-6 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;
- (b) 40-60 wt%  $\text{SiO}_2$ ;
- (c) 0-25 wt% MgO; and
- 15           (d) the remainder consisting essentially of CaO, the total being 100% by weight.

            11. The process of Claim 10 wherein the composition of subsection 1(c) ranges from 0.25-25 wt% MgO.

20           12. The process of Claim 1 wherein the composition consists essentially of:

- (a) 6-8 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;
- (b) 35-54 wt%  $\text{SiO}_2$ ;
- (c) 0-25 wt% MgO; and
- 25           (d) the remainder consisting essentially of CaO, the total being 100% by weight.

30           13. The process of Claim 12 wherein the composition of subsection 1(c) ranges from 0.25-25 wt% MgO.

SUBSTITUTE SHEET

-52-

14. The process of Claim 1 wherein the composition consists essentially of:

(a) 8-10 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 35-54 wt%  $\text{SiO}_2$ ;

(c) 0-20 wt%  $\text{MgO}$ ; and

(d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight.

15. The process of Claim 14 wherein the composition of subsection 1(c) ranges from 0.25-20 wt%  $\text{MgO}$ .

16. The process of Claim 1 wherein the fiber has a diameter of less than 3.5 microns.

17. The process of Claim 1 wherein the silicon extraction rate is at least 20 ppm, the  $\text{Al}_2\text{O}_3$  content is about 0.06-7 wt%, and the  $\text{SiO}_2$  content is about 40-66 wt%.

18. The process of Claim 1 wherein the silicon extraction rate is at least about 50 ppm, the  $\text{Al}_2\text{O}_3$  content is about 0.06-3 wt%, and the  $\text{SiO}_2$  content is about 40-60 wt%.

19. The process of Claim 1 wherein the silicon extraction rate is at least about 50 ppm, the  $\text{Al}_2\text{O}_3$  content is about 0.06-0.75 wt%, and the  $\text{SiO}_2$  content is about 40-60 wt%.

20. A process of protecting a structural wall from fire comprising the steps of:

**SUBSTITUTE SHEET**

-53-

1. providing a fiber blanket having a bulk density in the range of about 1.5 to about 3 lbs. per cubic foot (pcf); wherein the fiber blanket has the ability to pass ASTM E-119 two-hour fire test; the fibers in the blanket have a diameter less than about 3.5 microns; and the fiber is an inorganic fiber prepared from a composition consisting essentially of:

(a) 0-7 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 58-70 wt%  $\text{SiO}_2$

(c) 0-21 wt%  $\text{MgO}$ ;

(d) 0-2 wt% alkali metal oxide; and

(e) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight; and

2. placing the blanket next to the wall, and thereby protecting the wall from fire.

21. The process of Claim 20 wherein the composition of subsection 1(a) ranges from 0.06-7 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof.

22. The process of Claim 20 wherein the composition of subsection 1(c) ranges from 0.25-21 wt%  $\text{MgO}$ .

23. The process of Claim 20 wherein the composition consists essentially of:

(a) 0.06-3.0 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 58.5-70 wt%  $\text{SiO}_2$ ;

**SUBSTITUTE SHEET**

-54-

- (c) 0-21 wt% MgO;  
(d) 0-2 wt% alkali metal oxide; and  
(e) the remainder consisting essentially of CaO, the total being 100% by weight.

5

24. The process of Claim 20 wherein the composition of subsection 1(c) ranges from 0.25-21 wt% MgO.

10 25. The process of Claim 20 wherein the composition consists essentially of:

(a) from about 3 wt% up to and including 4 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

15

(b) 58-63 wt%  $\text{SiO}_2$ ;

(c) 0-8 wt% MgO;

(d) 0-2 wt% alkali metal oxide; and

(e) the remainder consisting essentially of CaO, the total being 100% by weight.

20

26. The process of Claim 25 wherein the composition in subsection 1(c) ranges from 0.25-8 wt% MgO.

27. The process of Claim 25 wherein the composition consists essentially of:

25

(a) from about 4 wt% up to and including 6 wt% of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 58-61 wt%  $\text{SiO}_2$ ;

(c) 0-7 wt% MgO;

30

(d) 0-2 wt% alkali metal oxide; and

**SUBSTITUTE SHEET**



-55-

(e) the remainder consisting essentially of  $\text{CaO}$ , the total being 100% by weight.

28. The process of Claim 25 wherein the composition of subsection 1(c) ranges from 0.25-7 wt%  $\text{MgO}$ .

29. An inorganic fiber having an average fiber diameter of less than about 3.5 microns, a silicon extraction rate greater than about 0.02 wt%  $\text{Si/day}$  in a physiological saline solution and having a composition consisting essentially of about:

(a) 0.06-5.0 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 35-70 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

(d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

30. An inorganic fiber having a silicon extraction of at least about 10 ppm over a 5 hour period in physiological saline solution and having a composition consisting essentially of about:

(a) 0.06-1.5 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-70 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt%  $\text{MgO}$ ; and

(d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

**SUBSTITUTE SHEET**

-56-

31. An inorganic fiber according to Claim 30 having a silicon extraction of at least about 20 ppm, an average fiber diameter of less than about 3.5 microns, and having an  $\text{SiO}_2$  content of about 40-66 wt%.

5 32. An inorganic fiber according to Claim 30 having a silicon extraction of at least about 50 ppm and having an  $\text{SiO}_2$  content of about 40-60 wt% and a MgO content of about 0.25-25 wt%.

10 33. An inorganic fiber having a silicon extraction of at least about 10 ppm over a 5 hour period in physiological saline solutions and having a composition consisting essentially of about:

15 (a) 1.5-3 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-66 wt%  $\text{SiO}_2$ ;

(c) 0-50 wt% MgO; and

20 (d) the remainder consisting essentially of CaO, the total being 100 wt%.

34. An inorganic fiber according to Claim 33 having a silicon extraction of at least about 20 ppm, an average fiber diameter of less than about 3.5 microns, and an MgO content of from about .25-50 wt%.

25 35. An inorganic fiber according to Claim 33 having a silicon extraction of at least about 50 ppm, an  $\text{SiO}_2$  content of from about 40-54 wt%, and an MgO content of from about 0.25-18 wt%.

30 36. An inorganic fiber having a silicon extraction of at least about 10 ppm over a 5 hour period

**SUBSTITUTE SHEET**

-57-

in physiological saline solutions and having a composition consisting essentially of about:

- 5 (a) 3-4 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;
- (b) 40-63 wt%  $\text{SiO}_2$ ;
- (c) 0-50 wt%  $\text{MgO}$ ; and
- 10 (d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

37. An inorganic fiber according to Claim 36 having a silicon extraction of at least about 20 ppm, an average fiber diameter of less than about 3.5 microns, and a  $\text{SiO}_2$  content from about 40-58 wt%.

15 38. An inorganic fiber according to Claim 37 having a silicon extraction of at least about 50 ppm and an  $\text{SiO}_2$  content of from about 40-52 wt% and a  $\text{MgO}$  content of from about .25-18 wt%.

20 39. An inorganic fiber having a silicon extraction of at least about 10 ppm over a 5 hour time period in a physiological saline solution and having a composition consisting essentially of about:

- 25 (a) 4-6 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;
- (b) 40-59 wt%  $\text{SiO}_2$ ;
- (c) 0-46 wt%  $\text{MgO}$ ; and
- 30 (d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

SUBSTITUTE SHEET

-58-

40. An inorganic fiber according to Claim 39 having a silicon extraction of at least about 20 ppm, an average fiber diameter of less than about 3.5 microns, and an  $\text{SiO}_2$  content from about 40-58 wt%.

5                   41. An inorganic fiber having a diameter of less than about 3.5 microns and which passes the ASTM E-119 two hour fire test when processed into a fiber blanket having a bulk density in the range of about 1.5 to 3 pcf, said inorganic fiber having a composition  
10 consisting essentially of:

(a) .06-7 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

15                   (b) 58-70 wt%  $\text{SiO}_2$ ;

(c) 0-21 wt%  $\text{MgO}$ ;

(d) 0.1-2 wt% alkali metal oxide;

and

(e) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%;  
20 wherein the amount of alumina + zirconia is less than 6 wt% and the amount of iron oxides or alumina + iron oxides is less than 2 wt%.

25                   42. An inorganic fiber according to Claim 41 having a composition consisting essentially of about:

(a) .06-1.5 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof; and

30                   (b) 58.5-70 wt%  $\text{SiO}_2$ .

SUBSTITUTE SHEET

-59-

43. An inorganic fiber according to Claim 42 having a silicon extraction of at least about 10 ppm over a 5 hour period in physiological saline solutions.

5 44. An inorganic fiber according to Claim 41 having a composition consisting essentially of about:

(a) greater than 1.5 wt% up to and including 3 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof; and

10

(b) 58.5-66 wt%  $\text{SiO}_2$ .

45. An inorganic fiber according to Claim 44 having a silicon extraction of at least about 10 ppm over a 5 hour period in a physiological saline solution.

15 46. An inorganic fiber according to Claim 41 having a composition consisting essentially of about:

(a) greater than 3 wt% up to and including 4 wt% material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

20

(b) 58-63 wt%  $\text{SiO}_2$ ;

(c) .25-8 wt%  $\text{MgO}$ ;

(d) .1-2 wt% alkali metal oxide;

and

25 (e) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

47. An inorganic fiber according to Claim 46 having a silicon extraction of at least about 10 ppm over a 5 hour period in physiological saline solutions.

SUBSTITUTE SHEET

-60-

48. An inorganic fiber according to Claim 41 having a composition consisting essentially of about:

(a) greater than 4 wt% up to and including 6 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 58-59 wt%  $\text{SiO}_2$ ;

(c) .25-7 wt%  $\text{MgO}$ ;

(d) .1-2 wt% alkali metal oxide;

and

(e) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

49. An inorganic fiber according to Claim 48 having a silicon extraction of at least about 10 ppm over a 5 hour period in physiological saline solutions.

50. An inorganic fiber having a silicon extraction of greater than about 0.02 wt% Si/day in a physiological saline solution, a continuous service temperature above about  $1450^\circ\text{F}$  and having a composition consisting essentially of about:

(a) .06-5 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;

(b) 40-70 wt%  $\text{SiO}_2$ ;

(c) 0-6 wt%  $\text{MgO}$ ; and

(d) the remainder comprising essentially of  $\text{CaO}$ , the total being 100 wt%.

51. The fiber of Claim 50 wherein the composition of subsection (c) has an amount of 0.25-6 wt%  $\text{MgO}$ .

SUBSTITUTE SHEET

-61-

52. An inorganic fiber having a silicon extraction of greater than about 0.02 wt% Si/day in a physiological saline solution, having a continuous service temperature above about 1500°F and having a composition consisting essentially of about:

- (a) .06-1.5 wt% of material selected from the group consisting of  $\text{Al}_2\text{O}_3$ ,  $\text{ZrO}_2$ ,  $\text{TiO}_2$ ,  $\text{B}_2\text{O}_3$ , iron oxides and mixtures thereof;
- (b) 60-70 wt%  $\text{SiO}_2$ ;
- (c) 0-1 wt%  $\text{MgO}$ ; and
- (d) the remainder consisting essentially of  $\text{CaO}$ , the total being 100 wt%.

53. The fiber of Claim 52 wherein the composition of subsection (c) has an amount 0.25-1 wt%  $\text{MgO}$ .

54. An inorganic fiber according to Claims 1 or 29 made from pure oxidic raw materials.

55. An inorganic fiber according to Claim 1 or 29 or 41 in which at least a portion of the raw materials is selected from a group consisting of talc, metallurgical slags, siliceous rocks, kaolin, and mixtures thereof.

56. An inorganic fiber having a composition consisting essentially of about:

(a) 8.0-9.3 wt%  $\text{Al}_2\text{O}_3$ ;

(b) 39-52 wt%  $\text{SiO}_2$ ;

(c) 22-38 wt%  $\text{CaO}$ ; and

(d) 7-14 wt%  $\text{MgO}$ , the total being 100 wt% and having a silica extraction in a saline solution of at least about 5 ppm over a 5 hour period.

SUBSTITUTE SHEET

-62-

57. An inorganic fiber composition having a composition consisting essentially of about:

(a) 49-61 wt%  $\text{SiO}_2$ ;

(b) 10-36 wt%  $\text{CaO}$ ; and

(c) 3-23 wt%  $\text{MgO}$ , the total being 100 wt% and having a  $\text{SiO}_2$  extraction in a saline solution of between about 24-67 ppm over a 5 hour period.

5

SUBSTITUTE SHEET